

**HIKVISION®**



# **KATALOG RETAIL** **2023**

[www.hikvision.com](http://www.hikvision.com)



#### DS-2CE76D0T-EXLPM

#### DS-2CE76D0T-EXLMF

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 25m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR ,OSD Menu (Up the Coax), IP67,2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67,2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal

- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR ,OSD Menu (Up the Coax), 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP67, 2.8/3.6/6mm Lens,
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : EXIR 30m IR  
3 : EXIR 40m IR  
5 : EXIR 80m IR



#### DS-2CE17D0T-IT1F

#### DS-2CE17D0T-IT3F

#### DS-2CE17D0T-IT5F

- 2MP CMOS Sensor, EXIR 30m IR,



#### DS-2CE16D0T-ITF

- 2MP CMOS Sensor, EXIR, 30m IR,
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12VDC,
- Smart IR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67,2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output
- Smart Lighting With Acusense DVR

# Teknologi Smart Hybrid Light

Pencahayaan pintar untuk memenuhi beragam kebutuhan

Menerangi jalan untuk keluarga dan tamu Anda dengan lampu otomatis  
Pada kondisi normal inframerah, mengeluarkan cahaya pada deteksi manusia atau kendaraan



White Light Mode Smart Mode IR Mode  
Smart switching between two supplemental lights



**DS-2CE16D0T-LPFS**

**DS-2CE16D0T-LFS**

- (P) : Plastic, (M) : Metal



**DS-2CE76D0T-LPFS**

**DS-2CE76D0T-LMFS**



**DS-2CE16D0T-EXLPF**

**DS-2CE16D0T-EXLF**

3 : EXIR 40m IR

5 : EXIR 80m IR



**DS-2CE56D0T-IT1F**

**DS-2CE56D0T-IT3F**

- HD1080p, 2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR,
- Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens,
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : EXIR 30m IR

- 3K SMP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 25m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



**DS-2CE76K0T-EXLMF**

- 3K SMP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output - Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



- 2MP CMOS Sensor, EXIR 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC,
- Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output



**DS-2CE5AH8T-AVPIT3ZF**

**DS-2CE59H8T-AVPIT3ZF**

**DS-2CE56H8T-AITZF**

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 60m IR, Auto Focus,
- Outdoor Vandal Proof Dome, ICR, up to 0.003 Lux/F1.2, 12 VDC/AC24V, Smart IR, True WDR, 3D DNR, OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output



# ANALOG 3K



## DS-2CE16K0T-LPFS

### DS-2CE16K0T-LFS

- V : Outdoor Vandal Proof Dome
- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light,
- indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial(Only TVI),
- Smart Lighting With Acusense DVR, OSD Menu(Up the Coax), 2.8/3.6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



## DS-2CE19H0T-AIT3ZF

### DS-2CE19H8T-AIT3ZF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 80m IR, Auto Focus,
- Outdoor Bullet, ICR, up to 0.003 Lux/F1.2, 12 VDC/AC24V, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (x) : 0 : Lux 0.01  
8 : Lux 0.003



## DS-2CE76K0T-LPFS

### DS-2CE76K0T-LFS



## DS-2CE16H8T-ITF

### DS-2CE16H8T-IT(x)F

### DS-2CE16H0T-ITPF(s)

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 30m IR,
- Outdoor EXIR Bullet, ICR, 0.003 Lux/F1.2, 12VDC, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (X) : 1 : 30m IR  
3 : 40m IR  
5 : 80m IR - 3K  
5MP 16:9 CMOS Sensor, 3K @ 20 fps  
(Default), EXIR, 20m IR+20m White Light,
- Outdoor Dual-light Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens Support TVI/AHD/CVI/CVBS video signal output - Smart Lighting With Acusense DVR
- (P) : Plastic, (M) : Metal



## DS-2CE57H0T-VPITF

### DS-2CE57H8T-VPITF



## DS-2CE16K0T-EXLF

- 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 30m IR,
- Outdoor Vandal Proof Dome, ICR, 0.003 Lux/F1.2, 12 VDC, Smart IR, True WDR, 3D DNR, OSD Menu (Up the Coax), IP67, 2.8/3.6/6/8/12mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (x) : 0 : Lux 0.01  
8 : Lux 0.003



## DS-2CE76H0T-ITPF(s)

### DS-2CE76H0T-ITMF

### DS-2CE76H8T-ITMF

- 5MP@20fps, 4MP@25fps(P)/30fps(N), EXIR, up to 30m IR,
- Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic, Audio up Coaxial(Only TVI),
- H0T : 0.01 Lux  
H8T : 0.003 Lux





**DS-2CE10DF3T-(P)F(S)**



**DS-2CE12DF3T-F(S)**



**DS-2CE72DF3T-FS**

- 2M BSI CMOS Sensor,
- Outdoor mini Bullet,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20M,3D DNR,DC 12V, OSD Menu (Up the Coax), 130dB True WDR, IP67, 2.8/3.6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- (S) : Built-in Mic,Audio up Coaxial(Only TVI)

- 2M BSI CMOS Sensor,
- Outdoor Bullet,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,40M,3D DNR,DC 12V, OSD Menu(Up the Coax), 130dB True WDR, IP67, 2.8/3.6/6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (S) : Built-in Mic,Audio up Coaxial(Only TVI),



**DS-2CE10DF0T-PF**

**DS-2CE10DF0T-F**

- 2M BSI CMOS Sensor, - 2M CMOS Sensor,
- Outdoor Turret,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,40M,3D DNR,DC 12V, OSD Menu(Up the Coax), 130dB True WDR, IP67, 2.8/3.6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (S) : Built-in Mic,Audio up Coaxial(Only TVI),

- Outdoor Bullet,0.001Lux/F1.0,0 Lux with white Light,20m,3D DNR,12 VDC,OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens,
- (P) : Plastic, (M) : Metal
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output



**DS-2CE70DF0T-PF**

**DS-2CE70DF0T-MF**

- 2M CMOS Sensor,
- Indoor Turret,0.001Lux/F1.0,0 Lux with white Light,20m,3D DNR,12 VDC,OSD Menu (Up the Coax), 2.8/3.6mm Lens,

- (P) : Plastic, (M) : Metal
- 24H Color, Support TVI/AHD/CVI/CVBS video signal output



**DS-2CE70DF3T-(P)F(S)**

- 2M BSI CMOS Sensor,
- Indoor Turret,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20M,3D DNR,DC 12V, OSD Menu(Up the Coax), 130dB True WDR, 2.8/3.6mm Lens,
- 24H Color,Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal

## 2MP



- (S) : Built-in Mic, Audio up Coaxial(Only TVI),



### DS-2CE12DF0T-F

- 2M CMOS Sensor,
- Outdoor Bullet, 0.001Lux/F1.0, 0 Lux with white Light, 40m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), IP67, 2.8/3.6/6mm Lens, - 24H Color, Support TVI/AHD/CVI/CVBS video signal output



### DS-2CE72DF0T-F

- 2M CMOS Sensor,
- Outdoor Turret, 0.001Lux/F1.0, 0 Lux with white Light, 40m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens, - 24H Color, Support TVI/AHD/CVI/CVBS video signal output

- 5M BSI CMOS Sensor, 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default),
- Outdoor Bullet, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 20m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), 130dB True WDR, IP67, 3.6/6mm Lens, - 24H Color Support TVI/AHD/CVI/CVBS video signal output
- 5M BSI CMOS Sensor, 5MP@20fps,



@ 20 fps(Default),

### DS-2CE10KF0T-PFS

### DS-2CE10KF0T-FS

- 3K 5MP 16:9
- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps(Default),

- 4MP@25fps(P)/30fps(N)(Default),
- Outdoor Turret, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 20m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), 130dB True WDR, IP67, 3.6/6mm Lens, - 24H Color Support TVI/AHD/CVI/CVBS video signal output
- 5M BSI CMOS Sensor, 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default),



- Outdoor Bullet, 0.0005Lux/F1.0, 0 Lux with Friendly Lighting, 40m, 3D DNR, 12 VDC, OSD Menu (Up the Coax), 130dB True WDR, IP67, 3.6/6mm Lens, - 24H Color Support TVI/AHD/CVI/CVBS video signal output

### DS-2CE12KF0T-FS

MOS Sensor, 3K



# 24/7

## Gambar Berwarna

# 5MP



**DS-2CE10HFT-F**

- Outdoor Bullet, 0.001Lux/F1.0, 0 Lux with white Light, 40m, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu IP67, 2.8mm/3.6mm Lens,
- 24H Color Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



**DS-2CE72HFT-F**

- Outdoor Bullet, 0.001Lux/F1.0, 0 Lux with white Light, 20m, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), (Up the Coax), IP67, 2.8mm/3.6mm Lens,
- 24H Color Support TVI/AHD/CVI/CVBS video signal output



**DS-2CE12HFT-F**

- Outdoor Bullet, 0.001Lux/F1.0, 0 Lux with white Light, 20m, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), (Up the Coax), IP67, 2.8mm/3.6mm Lens,
- 24H Color Support TVI/AHD/CVI/CVBS video signal output



- 3K 5MP 16:9 CMOS Sensor, 3K @ 20 fps(Default), - 3K 5MP Sensor, 3K @ 20 fps(Default),

- Indoor Turret, 0.001Lux/F1.0, 0 Lux with white Light, 40m, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), 2.8mm/3.6mm Lens,
- 24H Color Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal



**DS-2CE72KF0T-FS**

16:9 CMOS

- Outdoor Turret, 0.001Lux/F1.0, 0 Lux with white Light, 20m, 2D DNR, Built-in Mic, Audio up Coaxial(Only TVI), 12 VDC, OSD Menu(Up the Coax), IP67, 2.8mm/3.6mm Lens,
- 24H Color Support TVI/AHD/CVI/CVBS video signal output



**DS-2CE16U1T-IT(x)F**

**DS-2CE16U7T-IT(3)F**

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N),
- Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic
- U1T : 0.01 Lux, U7T : 0.003 Lux
- (X) : 1 : 30m IR, 3 : 60m IR, 5 : 80m IR



**DS-2CE57U1T-VPITF**

**DS-2CE57U7T-VPITF**

- 8.3MP @12.5fps(Default), 5MP@20fps, 4MP@25fps(P)/30fps(N), 2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Outdoor Vandal Proof Dome, ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP67, 3.6/6/8/12mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- U1T : 0.01 Lux
- U7T : 0.003 Lux





### DS-2CE76U7T-ITMF

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,
- Indoor EXIR Turret,ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- U1T : 0.01 Lux, U7T : 0.003 Lux

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 80m IR, Auto Focus ,
- Outdoor Bullet,ICR, 0.01 Lux/F1.2, Smart IR, DNR,OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output- (A) : 12VDC/AC24V

- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 60m IR, Auto Focus ,
- Indoor Dome,ICR, 0.01 Lux/F1.2,12 VDC/AC24V, Smart IR,DNR,OSD Menu(Up the Coax),2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output- (A) : 12VDC/AC24V



**DS-2CE19U1T-IT3ZF**

**DS-2CE56U1T-ITZF DS-2CE19U1T-IT3ZF**



**DS-2CE59U7T-AVPIT3ZF**

- 8.3MP @12.5fps(Default),5MP@20fps,

4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,

- Indoor EXIR Turret,ICR, up to 0.003 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens
- Support TVI/AHD/CVI/CVBS video signal output
- (P) : Plastic, (M) : Metal
- U1T : 0.01 Lux



0.005lux/F1.6, B/W:0.001lux/F1.6, Optical

Zoom:25x, Digital Zoom:16X,

- Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s,

- Up the Coax,100mIR,DC12V

**DS-2AE4225T-D DS-2AE4225T-D**

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR,

Ultra-low light Powerde By DarkFighter Color:

0.005lux/F1.6, B/W:0.001lux/F1.6,

- Optical Zoom:25x, Digital Zoom:16X,

- Up the Coax,DC12V



**DS-2CE5AU1T-AVPIT3ZF**

- 8.3MP @12.5fps(Default),5MP@20fps,

4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 60m IR, Auto Focus ,

- Outdoor Vandal Proof Dome,ICR, 0.01 Lux/F1.2, VDC/AC24V, Smart IR,DNR,OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens
- Support TVI/AHD/CVI/CVBS video signal output - (A) ; 12VDC/AC24V

U7T : 0.003 Lux



- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N), EXIR, 30m IR,

- Outdoor EXIR Turret,ICR, 0.01 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens

- Support TVI/AHD/CVI/CVBS video signal output

- U1T : 0.01 Lux, U7T : 0.003 Lux

- (X) : 1 : 30m IR, 3 : 60m IR



- 8.3MP @12.5fps(Default),5MP@20fps, 4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N),EXIR, 60m IR, Auto Focus ,

- Outdoor Turret,ICR, 0.01 Lux/F1.2,12 VDC, Smart IR,DNR,OSD Menu(Up the Coax), IP67, 2.7-13.5mm Motorized Vari-focal Lens

- Support TVI/AHD/CVI/CVBS video signal output

**DS-2AE4225TI-D**

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR, True WDR,

- Ultra-low light Powerde By DarkFighter Color:



# TURBO HD PTZ



## DS-2AE4215TI-D

- 1/2.8" CMOS, 1920x1080:30fps, TVI & CVBS output, 3D DNR,
- Ultra-low light Powerde By DarkFighter Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, Optical Zoom:15x,
- Pan Speed: 0.1° ~ 80°/s, Tilt Speed: 0.1° ~ 80°/s,
- Up the Coax,100m IR,DC12V

## DS-2AE4215T-D3

- 1/3" CMOS, 1920x1280:30fps, 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:15x, Focus:4.0-60mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -5°~90°(Auto Flip),
- Pan Speed: 0.1° ~160°/s, Tilt Speed: 0.1° ~120°/s,
- Up the Coax, 24VAC





eDVR Series

# Generation DVR untuk Masa Depan

SSD DVR Hikvision  
**DS-E04HQHI-B**



Mudah  
digunakan



Tanpa  
Instalasi



Hemat  
Waktu



**3** *Years*

**WARRANTY**  
GUARANTEED





# TURBO ACUSENSE DVR



**iDS-7204HQHI-M1/E**

**iDS-7208HQHI-M1/E**

**iDS-7216HQHI-M1/E**

- Full-channel motion detection 2.0 or 2/4-ch false alarm filter,
- Up to 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 16-ch video&1-ch audio input, H.265/H.265+ compression,
- 2-ch IP video input(up to 24-ch IP), 1 SATA interface
- CH01-04:1920×1080P @15 fps, 4MP Lite@15fps/ch, 260 1U case



**iDS-7204HUHI-M1/E**

**iDS-7208HUHI-M1/E**

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- Up to 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 8-ch HDTVI coaxial video&audio input, 1-ch RCA audio input,
- 4-ch IP video input(up to 16-ch IP), 1 SATA interface,
- H.265/H.265+ compression,
- 8MP: 8fps, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 260 1U case



**iDS-7204HQHI-M1/S**

**iDS-7208HQHI-M1/S**

**iDS-7208HQHI-M2/S**

**iDS-7216HQHI-M1/S**

**iDS-7216HQHI-M2/S**

**iDS-7232HQHI-M2/S**

- Full-channel motion detection 2.0 or 2/4-ch false alarm filter,
- Up to 32-ch Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 32-ch video&1-ch audio input, H.265/H.265+ compression, 1/2 SATA interface,
- 3MP @ 15fps, 1920×1080P @15 fps, 4MP Lite@15fps/ch, support CVBS output



**iDS-7204HUHI-M1/S**

**iDS-7208HUHI-M1/S**

**iDS-7204HUHI-M2/S**

**iDS-7208HUHI-M2/S**

**iDS-7216HUHI-M2/S**

- Full-channel motion detection or 4-ch false alarm filter,
- Up to 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 16-ch video&1-ch audio input, 1/2 SATA interface, H.265/H.265+ compression,
- 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, support CVBS output, stand alone 1U case



**iDS-7204HUHI-M1/S**

**iDS-7208HUHI-M1/S**

**iDS-7208HUHI-M1/S**

**iDS-7208HUHI-M2/S**

**iDS-7216HUHI-M2/S**

- Full-channel motion detection or 4-ch false alarm filter,
- Up to 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- Up to 16-ch video&1-ch audio input, 1/2 SATA interface, H.265/H.265+ compression,
- 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, support CVBS output, stand alone 1U case



**iDS-7204HTHI-M1/S**

**iDS-7204HTHI-M2/S**

**iDS-7208HTHI-M2/S**

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- Up to 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 1/2 SATA interface, H.265/H.265+ compression,
- 8 MP@12fps, 5 MP@20fps, 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), support CVBS output, standalone 1U case



**iDS-7316HQHI-M4/S**

**iDS-7332HQHI-M4/S**

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- Up to 32 Turbo HD/CVI / AHD / CVBS interface input,
- Up to 32-ch video&4-ch audio input, 4/16-ch IP video input(up to 48-ch IP), 2 RJ45 10M/100M/1000M self-adaptive Ethernet interface
- H.264/H.264+/H.265+/H.265 video compression, 4 SATA interface,
- 1920×1080P @15 fps, 4MP Lite @ 15fps/ch, Extended transmission distance over coax cable, 4K UHD output, 1.5U 19" case



**iDS-7316HUHI-M4/S**

- Full-channel motion detection 2.0 or 4-ch false alarm filter,
- 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,
- 16-ch video&4-ch audio input, 18-ch IP video input(up to 34-ch IP),
- H.264/H.264+/H.265+/H.265 video compression, 4 SATA interfaces,
- 8MP: 8 fps/ch, 5MP: 12 fps/ch, 4MP: 15 fps/ch, Extended transmission distance over coax cable, 4K UHD output, alarm I/O: 16/4, 1.5U 19" case



# 1 Series IPC



**DS-2CD1021G2-I**

- 1/2.8" Progressive CMOS, ICR,
- 1920x1080:25fps(P)/30fps(N), 2.8mm/F2.0 lens (4/6mm optional),



**DS-2CD1121G2-I**

- H.264+&H.264, IP67, DWDR, 3D DNR, BLC,
- IR range: up to 30m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect- 1/2.8" Progressive CMOS, ICR,



**DS-2CD1321G2-I**

- 1/2.8" Progressive CMOS, ICR,



- 1920x1080:25fps(P)/30fps(N),  
1920x1080:25fps(P)/30fps(N),  
2.8mm/F2.0 lens (4/6mm optional),  
2.8mm/F2.0 lens (4/6mm optional),
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080:  
25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264,  
DWDR, 3D DNR, BLC,
- IR or white light range: up to 30m,  
Built-in microphone, DC12V & PoE,
- Support mobile monitoring via Hik-Connect- (F): SD  
Card Slot (up to 256GB)
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080:  
25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264,
- H.264+&H.264, IP67,IK10, DWDR, 3D DNR, BLC - H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m,  
DC12V & PoE,
- Support mobile monitoring via Hik-Connect

Teknologi smart

# HYBRID LIGHT

Seri Ekonomis ColorVu

Alarm lampu hanya menyala tepat saat dibutuhkan



White Light Mode

IR Mode



Iluminasi Cahaya Hybrid  
yang Fleksibel



Target Kendaraan dan Manusia  
dengan Warna Asli



Lampu Peringatan  
kepada Penyusup



DS-2CD1043G2-LIU

DS-2CD1023G2-LIU

DS-2CD1023G2-LIUF

- 1/3" Progressive CMOS, ICR, DWDR, 3D DNR, BLC,
- IR or white light range: up to 30m, Built-in microphone, DC12V & PoE,



DS-2CD1143G2-LIU

DS-2CD1123G2-LIU

DS-2CD1123G2-LIUF

- 1/3" Progressive CMOS, ICR,
- Support mobile monitoring via Hik-Connect- (F) : SD Card Slot (up to 256GB) 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,



DS-2CD1323G2-LIU

DS-2CD1323G2-LIUF

- 1/3" Progressive CMOS, ICR, 1920x1080:
- IR or white light range: up to 30m, Built-in microphone, DC12V & PoE,
- Support mobile monitoring via Hik-Connect- (F) : SD Card Slot (up to 256GB)



- Warm light range: up to 30m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- UF: Build-in microphone & SD Card Slot (up to 256GB),
- IR or white light range: up to 30m, Built-in microphone, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- (F) : SD Card Slot (up to 256GB)



# ColorVu LITE

## Ekonomis & Berwarna

- F1.0 Super Aperture
- Sensor Canggih
- 30m Warm Light



**DS-2CD1327G2-L**

**DS-2CD1327G2-LUF**

**DS-2CD1347G2-L**

**DS-2CD1347G2-LUF**

- 1/2.7" Progressive CMOS, ICR, H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080: 25fps(P)/30fps(N),

- 1/3" Progressive CMOS, ICR,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,

- 1/2.7" Progressive CMOS, ICR, H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080: 25fps(P)/30fps(N),
- Warm light range: up to 30m, DC12V & PoE,
- Support mobile monitoring via Hik-Connect
- UF: Built-in microphone & SD Card Slot (up to 256GB),

- 1/2.7" Progressive CMOS, ICR, H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC,
- 4MP : 2560x1440: 20fps(P)/(N), 2MP : 1920x1080: 25fps(P)/30fps(N),

- H.264+/H.264/MJPEG;
- Color: 0.028 Lux @ (F2.0, AGC ON), 0 lux with IR;
- 25Fps/30fps(1920x1080);
- VCA functions; 2 streams; 3D DNR; BLC; ICR; EXIR, up to 10m; DC12V&PoE;
- Built-in mic&speaker; Built-in micro SD/SDHC/
- 2MP : 1920x1080:25fps(P)/30fps(N),

- 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC,
- Line crossing detection, Intrusion detection . IR range: up to 30m,
- HIK-Connect cloud service SDXC slot; HIK-Connect cloud service

- (up to 256GB),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC, Line crossing detection, Intrusion detection . IR range: up to 30m,
- Support on-board storage (SD card not included), HIK-Connect cloud service
- (S) : Audio/Alarm IO connectors

## The image displays two Hikvision security cameras against a dark blue background with light streaks. On the left is a bullet-style camera with a white upper body and a black lower body, mounted on a white base. On the right is a white dome-style camera with a lens array. Both cameras have the 'HIKVISION' logo printed on them.



**DS-2CD2121G0-IS**

- 1/2.8" Progressive CMOS, ICR, 0lux with IR,



- 1/2.8" Progressive CMOS, ICR, 0lux with IR, - 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D  
DNR, BLC, Line crossing detection,  
Intrusion detection . IR range: up to 30m,
- HiK-Connect cloud service - 1/2.8" Progressive CMOS, ICR, 0lux with IR
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D

- HIK-Connect cloud service
- 1/2.8" Progressive CMOS, ICR, 0lux with IR,
- 2MP : 1920x1080:25fps(P)/30fps(N),
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D

- Support on-board card slot



~~DS-2CD2721G0-IZ DS-2CD2721G0-IZ~~

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>- 1/2.8" Progressive CMOS, ICR, 0lux with IR,</li> <li>- 2MP : 1920x1080:25fps(P)/30fps(N), (F1.2; AGC ON),</li> <li>- H.265+/H.265/H.264/MJPEG, DC12V &amp; PoE, 3D DNR, BLC, ,Line crossing detection, Intrusion detection .IR: up to 30m,</li> <li>- Support on-board card slot (SD card not included), Vandal-proof, Hik-Connect cloud service</li> <li>- (S) : Audio/Alarm IO connectors</li> <li>- (Z) : Motorized VF lens</li> <li>- Powered by Darkfighter technology, Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;</li> <li>- 6 MP : 20fps(3200x1800), 4MP : 25fps/30fps (2688x1520), 2MP : 25fps/30fps (1920x1080);</li> <li>- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&amp;PoE;</li> <li>- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service;</li> </ul> | <ul style="list-style-type: none"> <li>- 1/2.8" Progressive CMOS, S, ICR, Color: 0.005 Lux @</li> <li>- 2MP : 1920x1080:25fps(P)/30fps(N),</li> <li>- Support on-board card slot</li> <li>- Powered by Darkfighter technology,</li> <li>- 6MP : 20fps(3200x1800), 4 MP : 25fps/30fps</li> <li>- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;</li> <li>- Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service: - (U) : built-in microphone</li> </ul> |
|---|--|



## DS-2CD2821G0

- (Z) : Motorized VF lens
- DS-2CD2821G0**
- Lux @
- H.265+/H.265/H.264/MJPEG, DC12V & PoE, 3D DNR, BLC,
- (SD card not included), HIK-Connect cloud service
- Audio/Alarm IO connectors.

- Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR;  
(2688x1520), 2MP : 25fps/30fps (1920x1080);  
ICR;  
EXIR, up to 30m; DC12V&PoE;

- (S) : Audio/Alarm IO

FOCUS  
and ACT

# AcuSense Technology



**YANG ANDA LIHAT**

APA YANG TIDAK AKAN ANDA LIHAT

Hingga  
**90%**  
dari alarm palsu  
yang disaring



**DS-2CD2063G2-I**  
**DS-2CD2063G2-IU**  
**DS-2CD2043G2-I**  
**DS-2CD2043G2-IU**  
**DS-2CD2023G2-I**  
**DS-2CD2023G2-IU**  
**DS-2CD2323G2-IU**

- 1/2.8" Progressive Scan CMOS; H.265+/H.265/  
H.264+/H.264/MJPEG;



**DS-2CD2163G2-I**  
**DS-2CD2163G2-IS**  
**DS-2CD2143G2-I**  
**DS-2CD2143G2-IS**  
**DS-2CD2023G2-I**  
**DS-2CD2123G2-IS**

- 1/2.8" Progressive Scan CMOS; H.265+/H.265/  
H.264+/H.264/MJPEG;



- 1/2.8" Progressive Scan CMOS; H.265+/H.265/ - 1/2.8" Progressive Scan CMOS; H.265+/H.265/  
H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, - Powered by Darkfighter technology,  
Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; - 6MP : 20fps(3200x1800), 4MP : 25fps/30fps  
- 6MP : 20fps(3200x1800), 4MP : 25fps/30fps (2688x1520), 2MP : 25fps/30fps (1920x1080); (2688x1520), 2MP : 25fps/30fps  
(1920x1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; - VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;  
EXIR, up to 30m; DC12V&PoE; EXIR; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; - Built-in micro SD/SDHC/SDXC slot;  
HIK-Connect cloud service; HIK-Connect cloud service;
- (U) : built-in microphone - (2I) model: up to 60m(2Leds) IR distance, - (4I) Model : up to 80m(4Leds) IR distance



**DS-2CD2463G2-I**  
**DS-2CD2443G2-I**  
**DS-2CD2423G2-I**

- 1/2.8" Progressive Scan CMOS;  
H.265+/H.265/MJPEG;
- Color: 0.008 lux@(F2.0, AGC ON), 0 lux with IR; - Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; - 6MP : 12.5fps/15fps(3200x1800), 4MP : 25fps/30fps  
- 6MP : 20fps(3200x1800), 4MP : 25fps/30fps (2688x1520), 2MP : 25fps/30fps (1920x1080); (2688x1520), 2MP : 25fps/30fps  
(1920x1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; - VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;  
EXIR, up to 10m; DC12V&PoE; EXIR, up to 30m; DC12V&PoE;
- Built-in mic&speaker; Built-in micro SD/SDHC/ - Built-in micro SD/SDHC/SDXC slot;  
SDXC slot; HIK-Connect cloud service; HIK-Connect cloud service;
- (S) : Audio/Alarm IO - (S) : Audio/Alarm IO



**DS-2CD2563G2-I**  
**DS-2CD2563G2-IS**  
**DS-2CD2543G2-I**  
**DS-2CD2543G2-IS**  
**DS-2CD2523G2-I**  
**DS-2CD2523G2-IS**

- 1/2.8" Progressive Scan CMOS;  
H.265+/H.265/H.264+/H.264/MJPEG;  
H.265+/H.265/H.264+/H.264/MJPEG;



**DS-2CD286G2-2I DS-2CD**  
**2CD2T46G2-2I DS-2CD2T**  
**2CD2T26G2-2I**  
**DS-2CD2T26G2-4I**  
- 1/2.7" Progressive Scan CMOS; H.265+/H.265/  
H.264+/H.264/MJPEG;  
Human / vehicle classification alarm, Powered by  
Darkfighter technology,

**DS-2CD2086G2-I DS-2C**  
**DS-2CD2146G2-**

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/  
H.264+/H.264/MJPEG;
- Human / vehicle classification alarm,  
Powered by Darkfighter technology,  
Color: 0.003 lux@(F1.6,  
AGC ON), 0 lux with IR;
- 8MP : 20fps(3840x2160), 4MP : 25fps/30fps  
(3072x1728, 2688x1520), 2MP : 25fps/30fps  
(1920x1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;

**DS-2CD2186G2-ISU**  
**DS-2CD2126G2-I**

- EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot;
- HIK-Connect cloud service
- (U) : built-in microphone



# DarkFighterX

FOCUS  
and  
ACT

## AcuSense Technology



**DS-2CD2386G2-I**

**DS-2CD2386G2-IU**

**DS-2CD2346G2-I**

**DS-2CD2346G2-IU**

**DS-2CD2326G2-I**

**DS-2CD2326G2-IU**

- Color: 0.003 lux@(F1.6, AGC ON), 0 lux with IR; - 8MP : 20fps(3840×2160), 4MP : 25fps/30fps (3072×1728, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
- S model: Audio/Alarm I/O
- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Human / vehicle classification alarm, Powered by Darkfighter technology, Color: 0.003 lux@(F1.6, AGC ON), 0 lux with IR;
- 8MP : 25fps/24fps(3840×2160), 4MP : 25fps/30fps (3072×1728, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- (S) model: Audio/Alarm I/O, (U) model: Built-in microphone



**DS-2CD2686G2-IZS DS-2C**

**DS-2CD2626G2-IZS**

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Human / vehicle classification alarm, Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR; - 8MP : 20fps(3840×2160), 4MP : 25fps/30fps

- (3072×1728, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
- Motorized Varifocal Lens
- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Human / vehicle classification alarm, Powered by Darkfighter technology, Color: 0.003 lux@(F1.6, AGC ON), 0 lux with IR;
- 8MP : 20fps(3840×2160), 4MP : 25fps/30fps (3072×1728, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot HIK-Connect cloud service
- (U) : built-in microphone



**DS-2CD2786G2-IZS DS-2C**

**DS-2CD2726G2-IZS**

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Human / vehicle classification alarm, Powered by Darkfighter technology,

- Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR; - 8MP : 20fps(3840×2160), 4MP : 25fps/30fps (3072×1728, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
- Motorized Varifocal Lens



**DS-2CD2086G2-IU/SL**

**DS-2CD2046G2-IU/SL**

**DS-2CD2026G2-IU/SL**

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 Lux @ (F1.4, AGC ON), 0 lux with IR;
- 4K : 25fps/24fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker

**DS-2CD2686G2-IZS**

**DS-2CD2646G2-IZS**

**DS-2CD2626G2-IZS**



- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Human / vehicle classification alarm, Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 8MP : 20fps(3840×2160), 4MP : 25fps/30fps (3072×1728, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
- Motorized Varifocal Lens



# Live Guard

Perlindungan proaktif, sepanjang hari



**DS-2CD2T86G2-ISU/SL**

**DS-2CD2T46G2-ISU/SL**

**DS-2CD2T26G2-ISU/SL**



- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;
- 4MP : 25fps/30fps (2688×1520); 2MP : 25fps/30fps (1920×1080);
- VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -(U) : Built-in microphone
- (SL) : Built-in microphone and speaker



**DS-2CD2386G2-ISU/SL DS-2C**

**ISU/SL DS-2CD2326G2-ISU/S**

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O



**DS-2CD2T86G2-ISU/SL**

**DS-2CD2646G2-IZSU/SL**

**DS-2CD2626G2-IZSU/SL**

- 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Powered by Darkfighter technology, Color: 0.003 lux@(F1.4, AGC ON), 0 lux with IR;
- 4K : 20fps(3840×2160), 4MP : 25fps/30fps (3200×1800, 2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 50m; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- Built-in microphone and speaker, Audio/Alarm I/O
- Motorized Varifocal Lens

-(U) : Built-in microphone



DS-2CD2T87G2-L

DS-2CD2T47G2-L

DS-2CD2T27G2-L



- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;

25fps/30fps(3200x1800); 4MP : 25fps/30fps (2688x1520), 2MP : 25fps/30fps (1920x1080); - Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; - Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; - U: Built-in microphone



DS-2CD2087G2-L

DS-2CD2087G2-LU

DS-2CD2047G2-L

DS-2CD2047G2-LU

DS-2CD2027G2-L

DS-2CD2027G2-LU

- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;  
- Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;  
- 4K : 25/24fps(3840x2160), 25fps/30fps(3200x1800); 4MP : 25fps/30fps (2688x1520); 2MP : 25fps/30fps (1920x1080); - Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE;

DS-2CD2147G2 DS-2CD21

DS-2CD2127G2 DS-2CD21

- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;

Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;

- 4K : 25/24fps(3840x2160), 25fps/30fps(3200x1800); 4MP : 25fps/30fps (2688x1520); 2MP : 25fps/30fps (1920x1080); - Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; - Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; - (U) : Built-in microphone



- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;

Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;

4K : 25/24fps(3840x2160),

## Perangkat Keras Mutakhir

aperture super besar hingga F1.0 dan sensor canggih

## Pemrosesan gambar yang terkini

Teknologi perintis ISP menghasilkan warna yang presisi untuk menampilkan gambar yang jelas dan tajam hingga 130 dB WDR



## Kehandalan Super Tinggi

Teknologi penyaluran aktif menjamin kinerja pemfokusan dalam produksi massal produk ColorVu berdefinisi ultra tinggi



ColorVu  
+ Panoramic



ColorVu  
+ Varifocal



ColorVu  
+ 4K



ColorVu  
+ Live Guard



ColorVu  
+ Deep Learning



- Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on;
- 4K : 25/24fps(3840×2160), 25fps/30fps(3200×1800); 4MP : 25fps/30fps (2688×1520), 2MP : 25fps/30fps (1920×1080);
- Human / vehicle classification alarm, VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE;
- Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;
- U:Built-in microphone

#### **DS-2CD2955FWD-I DS-2C1**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>- 1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;</li> <li>- Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR;</li> <li>- 5MP : 20fps(2944×1656), 25fps/30fps(2560×1440), 3MP : 25fps/30fps (2048×1536, 1920×1080);</li> <li>- 1.16mm@F2.2, field of view: 180°(H)×180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to</li> </ul> | <ul style="list-style-type: none"> <li>10m(optional); DC12V&amp;PoE; - Built-in micro SD/SDHC/SDXC slot;</li> <li>HIK-Connect cloud service</li> <li>- (S) : built-in mic, Audio/Alarm I/O</li> </ul> |
|---|---|



- 1/2.7" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.028 lux@(F2.0, AGC ON), 0 lux with IR; - 25fps/24fps (2688x1520); VCA functions; dual streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 10m;



#### DS-2CD2345G0P-I

- DC12V&PoE; - Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service
- 1/2.7" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;



#### DS-2CD2T45G0P-I

- Color: 0.028 lux@(F2.0, AGC ON), 0 lux with IR; - 25fps/24fps (2688x1520); VCA functions; dual streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 10m; DC12V&PoE; - Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service



- 4MP, 1/3" CMOS,H.265+/H.265/H.264+/H.264      - 4MP, 1/2.5" CMOS,H.265+/H.265/H.264+/H.264      - High quality imaging with 4MP / 2MP resolution

- 4MP : 2560 × 1440:30fps, Pan range:0°~330°; Tilt range: 0°~90°(Auto Flip), Pan Speed: 0.1° -100°/s, Tilt Speed: 0.1° -100°/s, 20m IR, POE&12VDC      - 4MP : 2560\*1440:30fps; 2MP : 1920\*1080:30fps.      - Pan and tilt ability enables camera to monitor zones of interest  
Pan Speed: 0.1° -80°/s, Tilt Speed: 0.1° -80°/s, PoE+&12VDC

- Smart Detection



**DS-2DE5225W-AE**

**DS-2DE5225W-AE3**

- 4MP, 1/2.5" CMOS,H.265+/H.265/H.264+/H.264  
codec, 3D DNR, True WDR, - Ultra-low light  
Powerde By DarkFighter  
Color: 0.005lux/F1.6, B/W:0.001lux/F1.6,  
- Optical Zoom:25x/15x, Digital Zoom:16X100m IR

# TandemVu

## 4-Inch PTZ Camera (SE4C)



Dual-channel  
video output



Fast linkage between  
video channels



Classified  
object detection



**DS-2DE3404W-DE**

**DS-2DE3204W-DE**

- High quality imaging with 4 MP / 2MP resolution
- Clear imaging against strong back lighting due to 120 dB WDR technology
- Pan and tilt ability enables camera to monitor zones of interest
- 4 × optical zoom allows for closer viewing of subjects in expansive areas
- Color: 0.1lux/F2.0, B/W:0.01lux/F2.0, Angle of View: 80-33.5 degree (Wide~Tele), Pan range:0°~350°; Tilt range: 0°~90°(Auto Flip), PoE&12VDC



**DS-2DE3A404IW-DE**

**DS-2DE3A404IW-DE/W**

- 4MP H.265+/H.265; 4x optical zoom;120 dB WDR; 12VDC & PoE;
- Powered by DarkFighter;IP66 ;Up to 50 m IR distance
- Built-in speaker and microphone for audible warning and two-way audio;
- White light flashing when alarm triggers
- (W) : Wifi



**DS-2DE3A400BW-DE**

- 4MP H.265+/H.265;120 dB WDR;12VDC & PoE;
- ColorVu;IP66 ;
- Built-in speaker and microphone for audible warning and two-way audio;
- White light flashing when alarm triggers
- Accurate human and vehicle target classification and alarm, based on deep learning algorithm
- Support face capture. Up to 5 faces captured at the same time



**DS-2DE4425IW-DE**

**DS-2DE4225IW-DE**

**DS-2DE4215IW-DE**

- codec 3D DNR, ICR,Color:
- 0.005lux/F1.6, B/W:0.001lux/F1.6,
- 4x optical zoom, Angle of View: 100° to 33° (Wide-Tele), Digital Zoom:16X,
- 4MP : 2560\*1440:30fps; 2MP : 1920\*1080:30fps. Pan Speed: 0.1° -80°/s, Tilt Speed: 0.1° -80°/s, PoE+&12VDC
- Smart Detection
- 25x optical zoom allows for closer viewing of subjects in expansive areas - Up to 50m IR range ensures safety at night - Water and dust resistant (IP66)



**DS-2DE4A225IW-DE**

**DS-2DE4A425IW-DE**

- Excellent low-light performance via powered-by-DarkFighter technology
- Clear imaging against strong back lighting due to 120 dB WDR technology
- High quality imaging with 4 MP/2 MP resolution
- Excellent low-light performance with powered by DarkFighter technology and ColorVu technology
- Secures an expansive area with 15x / 25x optical zoom and 16 × digital zoom
- Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus
- Expansive night view with up to 100 m IR distance & 30 m white light
- Supports 12 VDC & PoE+

**DS-2SE4C215MWG-E DS-**

**2SE4C415MWG-E DS-2SE**

- Captures a large area and great details at the same time

**DS-7104NI-Q1/M**

**DS-7608NI-Q1/M**

**DS-7108NI-Q1/M**

60Mbps Bit Rate Input Max (up to 4-ch IP video)

**DS-7604NI-Q1/4**

**DS-7108NI-Q1/M**

**DS-7608NI-Q1/M**

1 SATA interface, mini 1U case up to 6TB per HDD

**DS-7608NI-Q1/M**

**DS-7608NI-Q1/M**

**DS-7608NI-Q1/M**

**DS-7608NI-Q1/M**

# M-Series NVR



2 channels @ 32 MP, 8 @ 8 MP,  
16 @ 4 MP, or 32 @ 1080p  
decoding capacity

Up to 400 Mbps bandwidth  
for 64-channel NVRs, even  
with RAID enabled

8K or dual 4K resolution  
output, and up to 14 TB  
capacity per HDD



- 2-ch 1080P, or 1-ch 7M max
- Up to 160Mbps Bit Rate Input Max (up to 16-ch IP video), - 1/2 SATA



- interface, standalone 1U case, alarm I/O: 4/1(optional)
- Up to 160Mbps Bit Rate Input Max (up to 16-ch IP video), - 1/2 SATA interface,



- standalone 1U case, alarm I/O: 4/1(optional) - (xP) : Up to 16 port independent PoE network interface

**40Mbps**



**DS-7608NI-M2****128Mbps****DS-7608NI-M2/8P****128Mbps****DS-7616NI-M2****256Mbps****DS-7616NI-M2/16P****256Mbps**

- Up to 256Mbps Bit Rate Input Max (up to 16-ch IP video),
- 16x4MP decoding capability,HDMI up to 8K,
- 2 SATA Interfaces, alarm I/O: 4/1, 380 1U case
- (xP) : up to 16 independent PoE network interfaces,

**DS-7716NI-M4****256Mbps****DS-7716NI-M4/16P****256Mbps****DS-7732NI-M4****320Mbps****DS-7732NI-M4/16P****320Mbps**

- 320Mbps Bit Rate Input Max (up to 32-ch IP video),
- 32x2MP decoding capability, 4 SATA Interfaces, 2 HDMI outputs(up to 8K), 1 eSATA, alarm I/O: 16/9, 1.5U case,19"
- (xP) : 16 independent PoE network interfaces,

**DS-7604NXI-K1****40Mbps****DS-7608NXI-K1****80Mbps****DS-7616NXI-K1****160Mbps****DS-7608NXI-K2****80Mbps****DS-7616NXI-K2****160Mbps**

- False alarm reduction for up to 4-ch 1080P;
- Facial Recognition for up to 4 channels picture stream or 1 channels video stream;
- Support 16 face libraries, up to 10,000 face pictures in total;
- Up to 160Mbps Bit Rate Input Max (up to 16-ch IP video),
- H.265+/H.265/H.264+/H.264 video formats
- Adopt Hikvision Acusense technology to minimize manual effort and security costs

**DS-7604NXI-K1/4P****40Mbps****DS-7608NXI-K1/8P****80Mbps****DS-7608NXI-K2/8P****80Mbps****DS-7616NXI-K2/16P****160Mbps**

- False alarm reduction for up to 4-ch 1080P;
- Facial Recognition for up to 4 channels picture stream or 1 channels video stream;
- Support 16 face libraries, up to 10,000 face pictures in total;
- Up to 160Mbps Bit Rate Input Max (up to 16-ch IP video),
- plug & play with 16 Power-over-Ethernet (PoE) interfaces
- H.265+/H.265/H.264+/H.264 video formats
- Adopt Hikvision Acusense technology to

**DS-7716NXI-K4****160Mbps****DS-7716NXI-K4/16P****160Mbps****DS-7732NXI-K4****256Mbps****DS-7732NXI-K4/16P****256Mbps**

- False alarm reduction for up to 4-ch 1080P;
- Facial Recognition for up to 4 channels picture stream or 1 channels video stream;
- Support 16 face libraries, up to 10,000 face pictures in total;
- Up to 256 Mbps incoming bandwidth, Max(up to 32-ch IP video),
- (xP) : 16 independent PoE network interfaces,
- H.265+/H.265/H.264+/H.264 video formats
- Adopt Hikvision Acusense technology to

**DS-7716NXI-I4/S****256Mbps****DS-7716NXI-I4/16P/S****256Mbps****DS-7732NXI-I4/S****256Mbps****DS-7732NXI-I4/16P/S****256Mbps**

- False alarm reduction for up to 4-ch 1080P;
- Facial Recognition for up to 4 channels picture stream or 1 channels video stream;
- Support 16 face libraries, up to 10,000 face pictures in total;
- Up to 256 Mbps incoming bandwidth, Max(up to 32-ch IP video),
- (xP) : 16 independent PoE network interfaces,
- H.265+/H.265/H.264+/H.264 video formats
- Adopt Hikvision Acusense technology to

# K-Series NVRs with AcuSense





# PoE Switch

Cerdas • Kokoh • Aman



- L2, Unmanaged, Up to 8 x 10/100M RJ45 PoE ports, 1 x 10/100M RJ45 uplink port, - 802.3af/at, PoE power budget 60W, max. 250m long distance transmission, 6KV surge protection



- L2, Unmanaged, Up to 24 x 10/100M RJ45 PoE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, - 802.3af/at, PoE power budget up to 230W, "Extend" Mode port up to 250meter, 6KV surge protection



- L2, Unmanaged, Up to 24 Gigabit POE ports, 2 Gigabit SFP uplink ports, - 802.3af/at, PoE power budget up to 225w



**DS-3E0105P-E**

**DS-3E0109P-E**

**DS-3E0318P-E**

**DS-3E0326P-E**

- L2, Unmanaged, Up to 24 x 10/100M RJ45 PoE ports, 2 Gigabit combo ports, - 802.3af/at, PoE power budget up to 370W, "Extend" Mode ports support up to 250 meter, 6KV surge protection



**DS-3E0505P-E**

**DS-3E0510P-E**

**DS-3E0518P-E**

**DS-3E0526P-E**

- L2, Unmanaged, Up to 24 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, - 802.3af/at, PoE power budget Up to 370w



**DS-3E0505HP-E**

**DS-3E0510HP-E**

**DS-3E0520HP-E**

**DS-3E0528HP-E**

- Control and Preview
- L2, Unmanaged, Up to 24 Gigabit RJ45 PoE ports, 2 Gigabit RJ45, 2 Gigabit SFP uplink ports, - 802.3af/at/bt, Up to 4 port support Hi-PoE 90w, PoE power budget up to 370W, Extend mode support up to 300meter, 6KV surge protection, - supports POE watchdog, port isolation



**DS-3E1105P-EI**

**DS-3E1309P-EI**

- L2, Smart Managed, Up to 8 x 10/100M RJ45 PoE ports, 1 10/100 Mbps or Gigabit RJ45 port, - 802.3af/at, PoE power budget 110W, Max. 300 meter PoE transmission, - Supports Hik-Central/iVMS 4200/ HikPartner-Pro Unified Topology Management, cloud management, health monitor



**DS-3E1510P-SI**

**DS-3E1518P-SI**

**DS-3E1526P-SI**

- L2, Smart Managed, Up to 24 Gigabit PoE ports, 2 Gigabit SFP ports, - 802.3af/at, PoE power budget up to 370W, max. 300 meter long distance PoE transmission, - PoE watchdog, VLAN, QoS, SNMP, Port Mirroring, Storm Control, Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push and Video



**DS-3E0106HP-E**

**DS-3E0310HP-E**

- L2, Unmanaged, Up to 8 x 10/100M RJ45 PoE ports, 2 Gigabit RJ45 uplink ports, - 802.3af/at/bt, port 1 support HiPoE 60w, PoE power budget up to 110W, max. 250m long distance transmission, 6KV surge protection



## Produk NON-CCTV



### DS-KD8003Y-IME2

- Two-wire version: CMOS 2MP HD Colorful Camera, Fish eye (Horizontal: 180°, Vertical: 96°), 1 Call Button, 2-ch Indoor



### DS-KIS702

- IP video intercom kit for villa or house, only one call button.
- DS-KD8003-IME2/Surface x 1; - Include one monitor, one outdoor panel,
- DS-KH6320-WTE2 x 1; 5-meter 4-wire cable, and other



- No need additional power supply, but

### DS-K1T801M

- Standalone Access Control Terminal, Built-in Mifare card reading module, - Storage with 3,000 cards; 12 Keys keyboard and doorbell, DC 12V/1A



### DS-KH6320Y-WTE2

- station access - IR Supplement, 10M/100M Self-adaptive Ethernet, module connection with RS-485, 4-ch alarm input
- IP65, Two -wire interface, 98mmx99.8mmx 43.9mm



### DS-KIS202 (NEW)

- Analog Kit
- Kit including DS-KB2411-IM and DS-KH2220

### DS-KIS702Y

### DS-KIS203(NEW)

- Indoor station 7-inch Colorful TFT LCD, display resolution: 1024 \* 600; - 10/100Mbps Ethernet, Wi-Fi 802.11b/g/n; standard PoE/ 12 VDC. - TF card, max 32G; 8-ch alarm input, 2xalarm output, 1x485
- DS-KAD704 x 1; accessories
- DS-KAW30-2N x 1; - you have to mark which standard adapter
- 16GB TF card x1; you want when you place an order
- No need additional power supply
- Water Proof Analog Kit
- Kit including DS-KB2421IM and DS-KH2220 - Include one monitor, one metal outdoor panel, 5-meter 4-wire cable, and other accessories
- you have to mark which standard adapter you want when you place an order

### DS-KIS604-P

- IP video intercom kit for villa or house, only one call button.
- DS-KV8113-WME1 x1;
- DS-KH6320-WTE1 x1;
- 4 port standard PoE switch x1; (for KIS604-S)
- PSU x2; (for KIS604-P)
- 16GB TF card x1;

you have to mark which standard of power line type of the PoE switch you want when you place an order. (for KIS604-S)  
It includes 2 European power adapters, if you want to change the standard of

power supply, you have to mark which standard of power adapter you want when you place an order. (for KIS604-P)

- 3,000 cards, 3,000 fingerprints and 100,000 access control events;
- Support Access Control and Time Attendance Function, Optical Fingerprint Module;
- Uplink Communication: TCP-IP, WIFI; Supports Wiegand, Supports ISUP5.0, ISAPI
- Multiple languages: English, Spanish,

### DS-K1T804AEF

- 2.4 inch LCD Display Standalone Access Control Terminal, Built-in Mifare card (M) or EM card (E) reading module, - Storage with

# DS-K1T8003MF

- Terminal akses kontrol sidik jari  
Layar LCD 2,4 inci dibekali dengan modul pembaca kartu Mifare, Komunikasi:TCP/IP, Ehome
- Kapasitas 1000 pengguna, 1000 sidik jari, 1000 kartu Mifare dan Maks. 100.000 catatan kejadian;
- Mendukung Kontrol Akses dan Fungsi Absensi, modul optic sidik jari;
- Mendukung 6 status kehadiran, termasuk jam masuk, jam pulang, istirahat dimulai, istirahat selesai, lembur di mulai, lembur selesai
- Membuka pintu dari jarak jauh melalui klien seluler Hik-Connect, tamper alarm.



Italian, French, Portuguese (Brazilian),  
Vietnamese, Arabic, Thai, Turkish,



Indonesian, Ukrainian



Module;

- Uplink Communication: TCP-IP, WIFI; Supports Wiegand, Supports ISUP5.0, ISAPI
- multiple languages: English, Spanish, Italian, French, Portuguese (Brazilian), Vietnamese, Arabic, Thai, Turkish, Indonesian, Ukrainian

**DS-K1T804BEF**

**DS-K1T804BMF**

- 2.4 inch LCD Display Standalone Access Control Terminal, Built-in Mifare card (M) or EM card (E) reading module, - Storage with 3,000 cards, 3,000 fingerprints and 100,000 access control events;
- Support Access Control and Time Attendance Function, Optical Fingerprint





500 Faces 1k Cards  
1k Finger Print 2.4"

### DS-K1T320MFX DS-K1T320EFX

- Terminal Pengenalan Wajah, layar LCD 2,4 inci, 2 Mega piksel lensa sudut lebar,Built in-M:Modul membaca kartu Mifare, E:EM Modul pembaca kartu proksimiti
- kapasitas Maks.500 wajah, 1.000 sidik jari,1.000 kartu
- Pengenalan wajah di lingkungan gelap, Konfigurasi melalui klien web
- Mendukung TCP/IP,DC 12V/1A, Mendukung ISUP5.0, ISAPI
- Mendukung 6 status kehadiran, termasuk jam masuk, jam pulang, istirahat dimulai, istirahat selesai, lembur di mulai, lembur selesai
- Beberapa bahasa: Inggris, Spanyol (Amerika Selatan), Arab, Thailand, Indonesia, Rusia, Vietnam, Portugis (Brasil), Jepang, Korea
- Tingkat Akurasi Pengenalan Wajah > 99%, Durasi(1:N) ≤ 0,2 detik, Jarak: 0,3m ~ 1,5m



DS-K1T343MFX

DS-K1T343MX

DS-K1A340



- Face Recognition Terminal (A : Time Attendance only) , 4.3-inch LCD touch screen,2 Mega pixel wide-angle lens,Built-in Mifare card reading module (M);
- Max.1,500 faces capacity Max.3,000 cards (M); Max.3,000 fingerprints capacity (F), up to 300,000 attendance records - Face recognition in dark environment, IP65, - Two-way audio with client software, indoor station, and

- master station - Supports TCP/IP (Only T Model), DC 12V/1A, Supports ISUP5.0, ISAPI - Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out - (A) Support Local Attendance
- multiple languages: English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil) - Configuration via the web client
- Face Recognition Accuracy Rate > 99%, Duration(1:N) ≤0.2s, Distance: 0.3m ~ 1.5m

- Face Recognition Terminal, 4.3-inch LCD touch screen,2 Mega pixel wide-angle lens,Built-in Mifare card reading module;- Max.1,500 faces capacity Max.3,000 cards;Max.3,000 fingerprints capacity (F) - Face recognition in dark environment, IP65, Configuration via the web client - Two-way audio with client software, indoor station, and master station - Supports TCP/IP, WiFi,DC 12V/1A, Supports ISUP5.0, ISAPI
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in,



overtime out - multiple languages: English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)	- Face Recognition Terminal, 4.3-inch LCD touch screen, 2 Mega pixel wide-angle lens, Built-in Mifare card reading module; - Max. 3000 faces capacity and Max. 1500 fingerprints capacity (F), Max. 3000 cards; - Face recognition in dark environment, IP65, - Two-way audio with client software, indoor station, and master station - Supports TCP/IP, DC 12V/3A, Supports	Ehome5.0, ISAPI - Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out - Face Recognition Accuracy Rate > 99%, Duration(1:N) ≤ 0.2s, Distance: 0.3m ~ 1.5m
- Face Recognition Accuracy Rate > 99%, Duration(1:N) ≤ 0.2s, Distance: 0.3m ~ 1.5m		- Four 5-dBi amplified antennas - Beamforming optimizes signal - Dual band – Smart signal switching
- Data Rate: 2.4 GHz: 300 Mbps Antenna: Two 5-dBi amplified antennas Wireless Standard: IEEE 802.11b/g/n @ 2.4 GHz		

# Kecepatan Koneksi Lancar di Setiap Kesempatan

## Router Nirkabel Hikvision

Memberikan pengalaman online yang paling cerdas & Berkecepatan tinggi



### Antena 5-dBi

Antena omnidirectional yang sangat sensitif



### Sinkronisasi Akun

Dapatkan akun broadband secara otomatis dari router sebelumnya



### Dual Band

Auto switch antara sinyal 2,4 & 5 GHz



### Manajemen yang Nyaman

Mendukung web dan Aplikasi Hik-Connect dengan fungsi yang luas



### Beamforming

Sesuaikan bentuk gelombang ke balok agregat ke arah pengguna



### MU-MIMO

Koneksi serentak dan lancar dengan lebih banyak perangkat



#### DS-3WR3N

- 5-dBi amplified antennas
- Dual antennas for maximum coverage
- Supports IPTV

- Working Frequency Band: 2.4 GHz- Data Rate: 5 GHz: 867 Mbps; 2.4 GHz: 300 Mbps  
Antenna: Four 5-dBi amplified antennas



#### DS-3WR12C

- Broadband account synchronization

Wireless Standard: IEEE 802.11/a/n/ac wave 2 @ 5 GHz; IEEE 802.11b/g/n @ 2.4 GHz Working Frequency Band: 2.4 GHz, 5 GHz

# Hikvision Kabel Jaringan Pilihan Pertama, Selamanya Terpercaya

Pilihan untuk

Sistem CCTV

99.95%  
Kemurnian Cu



Konduktivitas yang lebih tinggi  
dengan redaman transmisi  
sinyal yang lebih rendah

0.565 mm  
Diameter Kawat



Transmisi sekarang lebih  
stabil dengan resistensi  
yang berkurang

Lapisan  
tahan Api

Bahan tebal tahan terhadap api,  
peregangan, dan penuaan



Peningkatan kemudahan  
aliran ke data transmisi



Teknologi memutar  
yang tepat



**DS-1LN5E-E/E**

- UTP CAT 5E, 305 meters,
- Core diameter: 0.45mm
- OFC,CMX ,gray



**DS-1LN6U-G**

**DS-1LN6U-W/CCA**

- UTP CAT 6, 305 meters
- Core diameter: 0.585mm,CCA,white
- Core diameter: 0.55mm Solid Copper, gray



